

SPC2-525 / SPC2-650
SPS2-650 / SPC3-690

I N - C A R E N T E R T A I N M E N T



 Nakamichi®

Pure Grit

There is no doubt a good amplification is conceivably the bedrock of mobile speaker system, the crave for high quality speaker sound is inevitable. Enhance your car audio with the latest range of Nakamichi Mobile Speaker Systems.

With high-grade polypropylene and membrane polyglass woofer cone supported by unique suspension rubber, solid-deep low frequency reproduction is discharged. Tweeters embodied with silver mylar and silk dome yield accurate high frequency response. All speakers are built-in with ferrite magnet and perform up to 150 watts music power handling. Tactfully selected and precise engineered, these Nakamichi Mobile Speaker Systems are designed to deliver a new dimension and ethos in harmony of sound perfection.

Features

- Unique Suspension Rubber Surround Woofer
- High-grade Polypropylene / Membrane Polyglass Woofer Cone
- Ferrite Magnet On All Speakers
- Silver Mylar / Silk Dome Tweeters
- Handles Up To 150 Watts Music Power

Specifications



Model	SPC2-525	SPC2-650	SPS2-650	SPC3-690
Speaker Features				
Speaker Type	5.25" Coaxial Speaker System	6.5" Coaxial Speaker System	6.5" Component System	6" x 9" Tri-axial Speaker System
Speaker Design	2-Way	2-Way	2-Way	3-Way
Power				
Sensitivity	87 ± 2 dB	87 ± 2 dB	89 ± 2 dB	90 ± 2 dB
Impedance	4 ohm	4 ohm	4 ohm	4 ohm
Response Bandwidth	80 - 20 kHz	65 - 20 kHz	55 - 20 kHz	45 - 21 kHz
Power Handling { RMS }	35 Watts	45 Watts	70 Watts	75 Watts
Power Handling { Peak }	70 Watts	90 Watts	140 Watts	150 Watts
Miscellaneous				
Tweeter V. Coil Size	20 mm / 0.75"	20 mm / 0.75"	25 mm / 1"	13 mm / 0.5"
Tweeter Cone / Dome	Silk Dome	Silk Dome	Silk Dome	Silver Mylar
Woofer Cone	Polypropylene / Aluminium Vapor Deposited	Polypropylene / Aluminium Vapor Deposited	Membrane Polyglass Paper Cone	Polypropylene / Aluminium Vapor Deposited
Woofer Surround	Suspension Rubber Surround	Suspension Rubber Surround	Suspension Rubber Surround	Suspension Rubber Surround
Woofer Frame	Stamped Steel Basket With Spray Black Wrinkle PP	Stamped Steel Basket With Spray Black Wrinkle PP	Cast Aluminium Basket Multi Mount Black Anodized With Machined Edge Trim	Stamped Steel Basket With Spray Black Wrinkle PP
Magnet Type	14 oz Ferrite	14 oz Ferrite	20 oz Ferrite	20 oz Ferrite
Mounting Depth Bottom Crossover	HP External 6 dB / Octave	HP External 6 dB / Octave	LP External 12 dB / HP External 12 dB Octave	
Mid-Range V. Coil Size				13 mm / 0.5"
Mid-Range Cone / Dome				Silver Mylar

Authorised Distributor's Stamp

**Dimensions do not include protruding parts. Specifications and design are subject to change for further improvement without notice.*

